

Section 10 – Mini Stocks 2023+ (Meridian & Magic Valley)

10.1 DEFINITION.

- 10.1.1 The word stock will mean unaltered as originally factory produced and installed for make. All Cars and trucks will be stock unless otherwise specified within these rules.

10.2 COMPETING MODELS.

- 10.2.1 1960 newer 4 cylinder sedans, coupes, or pickups.
10.2.2 Any front or rear wheel drive non-turbo 4 cylinder approved. Fiero and 2 seat sports car models not approved.

10.3 ENGINES

- 10.3.1 May be OEM engine, will be make to make swaps ok. 4 cylinder only.
10.3.2 Only factory produced OEM parts and components will be approved unless otherwise specified.
10.3.3 Connecting rods of aftermarket supply are approved of similar weight and material
10.3.4 Intake manifold will be stock with factory casting numbers. No porting. No grinding or modifications of any kind allowed other than the 4 hole aluminum intake for 2.3 Fords and Chevy Monza, plenum (plenum means inside of manifold) area may be cut down 1" maximum in order to run the class carburetor. Must pass tech approval.
10.3.5 Header or exhaust manifold type is optional
10.3.6 Flywheel may be cut or surfaced but must retain factory casting numbers.
10.3.7 Clutch disc and pressure plate will be stock type replacement only.
10.3.8 No porting of cylinder heads allowed.
10.3.9 Stock type rocker arm assembly only.
10.3.10 Pistons, valves, and valve springs may be factory type replacement of similar weight and material.
10.3.11 SPRINGS/RETAINERS/LOCKS– May be aftermarket to match cam. Double Springs O.K. May machine heads to use double springs.
10.3.12 Fuel pumps must be factory type replacement. Electric pumps must have oil pressure shutoff switch. (If engine dies, fuel pump must shut down immediately.)
10.3.13 Engine must remain in stock location.
10.3.14 One two-barrel carburetor only. Any OEM 2bbl carb, or Holley 7448 or 4412 approved. Maximum 1" adapter or spacer plate allowed. Two Throttle return spring will be required.
10.3.15 Injection cars must have OEM fuel log, intake and throttle body.
10.3.16 Air cleaner or butterfly cover required.
10.3.17 Oil pans may be over-sized, interior baffles allowed. Claimer pan approved. Oil coolers and remote filter locations are approved. Oil coolers must be mounted outside of the driver's compartment. Must be located forward of the front firewall and rearward of the radiator.
10.3.18 Camshafts may be after-market type of any manufacturer. Roller cam and lifters not approved, unless OEM for engine being used.
10.3.19 Cam timing gear is optional.
10.3.20 After market and speed parts not approved in the above section will be subject to removal at track discretion.

10.4 BODY SPECIFICATIONS

- 10.4.1 Body and chassis must be of the same make and model.
10.4.2 Body must be complete for declared make and model. Aftermarket steel panels approved. Nose cone and hood and fenders may be of any material if repurposing latemodel noses, fenders ect., all installation shall be aesthetically correct and in good shape.
10.4.3 Bodies to remain stock in appearance. Destroyed panels must be replaced or repaired.

- 10.4.4 Fenders and quarter panels may be trimmed for tire clearance. Trimming not to exceed 3" from top of the tire.
- 10.4.5 All exterior molding and lights must be removed. Including rear and side glass.
- 10.4.6 Windshield optional. If removed it is recommended that it is replaced with a maximum of ½" X ½" mesh screen covering the entire opening and be securely mounted. Lexan windshields are approved. Windshield opening must have one or two "tire bars" securely welded into opening to prevent a tire like object from entering the driver's compartment. Mirrors optional.
- 10.4.7 Front inner fenders may be removed. Both inner door panels may be removed. All other inner panels must retain stock location and be complete. Hood and rear deck lid, roof panel and inner quarters may be skinned. A hole in the hood may be cut to allow air cleaner clearance.
- 10.4.8 Inner panels in trunk area may be removed/replaced.
- 10.4.9 Exterior nerf bars optional. Nerfing not to extend more than 1 ½" past the body skin at any time, ends must be capped or welded shut. Nerfing allowed on both sides, between front and rear tires only. 1" O.D. round or maximum 1" X 2" square tubing is the only approved material for exterior Nerfing.
- 10.4.10 Rear Spoilers are optional. Side board and side panels not approved

10.5 BUMPERS

- 10.5.1 Bumpers will be stock for make and model.
- 10.5.2 Fabricated tube style bumper may be used if covered by a factory stock rubber bumper cover or After-market front bumper cover.
- 10.5.3 All rear bumper covers may be stock or aftermarket type.
- 10.5.4 Front and rear bumpers may be strapped to the fenders or quarter panels with a minimum 1/8" thick steel strap. Recommended piece 1 ½" X 12" should be securely bolted or welded in place, unless covered by a bumper cover.
- 10.5.5 Front bumper may be reinforced for radiator protection.
- 10.5.5.1 Two upright bars and two cross bars not to extend beyond the front bumper.
- 10.5.5.2 Not to be connected to the roll cage in any way.
- 10.5.5.3 Exception, rule number 10.6.5 below.

10.6 ROLL CAGE

- 10.6.1 A six-point roll cage is mandatory. The roll cage must be mounted to the frame, maximum seven points to the frame.
- 10.6.2 Main bars must be a minimum 1 1/4" black pipe, 2" O.D. maximum, with a 1/8" wall thickness, weld or securely bolt to the frame. Braced not less than half the height of the main bar back to the frame. At least one diagonal brace in main bar. Minimum three sissy bars on driver's side and two on the right passenger side.
- A minimum 1 1/2" O.D. roll bar tubing or manufactured roll cage kits are acceptable. **No exhaust tubing or galvanized pipe allowed.**
- 10.6.3 Gussets are required on all 90-degree joints.
- 10.6.4 Unibody. Roll cage must be securely fastened to the floorboards by welding 1/8" thick minimum plate, 4" X 8" or 6" X 6" on top and/or underneath the floorboards using 3/8" bolts per mounting, or cage may be directly integrated into the sub frame at all main points with full circumference welds.
- 10.6.5 Front hoops allowed to penetrate the firewall. Hoop bracing intergrated into strut towers is approved. Radiator support may be integrated into the hoop. All mounting to be ahead of the upper A-arms.

10.7 TRANSMISSION

- 10.7.1 Automatic transmission use is optional.
- 10.7.2 Transmission must be stock for make.
- 10.7.3 Torque converters will stock stall speed.
- 10.7.4 Transmission coolers and cooler lines shall be contained outside of the driver's compartment. It also must be located in front of the front firewall or behind the rear firewall, no exceptions.
- 10.7.5 Manual gearboxes will be stock for make with no alterations. Gearing optional

10.8 REAR END

- 10.8.1 Must be stock for make and model.
- 10.8.2 Gear ratio optional.
- 10.8.3 Unlocked differentials are optional

10.9 SUSPENSION

- 10.9.1 Suspension must be stock with the following exceptions.
- 10.9.2 Shocks and struts must be stock type and mount in original location. Notching of Strut tower bolt holes is permitted. Replacement tower plate approved
- 10.9.3 Front coil spring type, size and height is optional. No adjustable spacers on top of the spring allowed. No weight jacking bolts or devices of any kind allowed. Torsion bars will be stock or stock type replacement only. An adjustable spacer welded "solid" is approved.
- 10.9.4 **Leaf spring cars** will remain leaf spring cars. Stacks may be altered. Any spacers or lowering blocks used in the leaf stack must be securely mounted. Front mounts will be stock. Rear shackles/connectors may be stock or fabricated. No threaded or adjustable jacking devices approved. No chains or stopper may be used to stop suspension movement.
- 10.9.5 Use of twisties or spring rubbers are approved.
- 10.9.6 **Rear coil** springs of any type approved. Shims or spacers of any type may be used to raise or lower either corner of the car. No permanent or weld-in; threaded or adjustable jacking devices approved. Spring pockets may be altered or replaced, but will remain in stock location.
- 10.9.7 **Sway bars** will remain stock for make and must be mounted in stock location. Connection method to lower control arms is optional. Sway bars may be adjustable. Poly bushings approved. No heating, cutting, welding, grinding, or bending of any suspension component allowed, unless otherwise noted.
- 10.9.8 A-arms must be stock for MAKE AND MODEL, this means: UPPERS AND LOWERS. Poly or steel bushings approved.

10.10 BRAKES

- 10.10.1 All four corners must be stock and in working order. Stock swaps for larger or disc brakes allowed in front.
- 10.10.2 Rear disc brakes are not allowed, unless stock for make and model.

10.11 WHEELS

- 10.11.1 Steel Wheel not to exceed 8" in width. White spoke type wheel or better mandatory on the right front corner, not to exceed 8" in width.
- 10.11.2 13" or 14" or 15" wheels are approved.

10.12 TIRES

- 10.12.1 Hoosier 700
23.5/8-13 (previous year 7" tires approved)
23.0/8-13 (previous year 7" tires approved)
Previous year 15" 700 version hoosier approved
- 10.12.2 Chemical softening of tires is prohibited.

10.13 RADIATOR

- 10.13.1 Only one radiator allowed.
- 10.13.2 Must mount in stock location.
- 10.13.3 One gallon over flow tank required.

10.14 FUEL SUPPLY

- 10.14.1 Commercially produced fuel cell is mandatory. See Speedway Specs for installation instructions. exception: stock gas tank may be used and must remain in place if it is located forward of rear axle.
- 10.14.2 Rubber line passing through the driver's compartment will be contained in conduit or pipe from the front firewall to the rear firewall.
- 10.14.3 Racing fuel approved, no alcohol allowed. E-85 approved.

10.15 ELECTRICAL

- 10.15.1 Ignition will remain stock for make, after-market coils and/or replacement ignition modules are approved. Distributors will remain stock for make, HEI and single point approved. Stock ECU may be tunable.
- 10.15.2 Alternator is optional. Car must start on its own power.
- 10.15.3 See Speedway Minimum Specifications for battery mounting requirements.

10.16 SEAT

- 10.16.1 Aluminum racing seat required. Steel framework around the seat is recommended. Installation is subject to tech approval.

10.17 ENGINE FAN

- 10.17.1 Mechanical or electric fan only, after-market allowed.
- 10.17.2 Fan must be shrouded, must cover both sides and top.

10.18 FIRE EXTINGUISHER

- 10.18.1 Participants car must be equipped with a 2 ½ lb fire extinguisher within easy reach of the driver, must be full at all times and have a readable gauge.
- 10.18.2 Each participant must keep a second fire extinguisher in his/ her pit area. The extinguisher will be a minimum 2 ½ lb or larger.

10.19 SAFETY ITEMS & MUFFLERS

- 10.19.1 SEE SPEEDWAY MINIMUM SPECIFICATIONS FOR ALL SAFETY ITEMS THAT ARE APPLICABLE TO YOUR CLASS.
- 10.19.2 Left side window net will be fitted with a seatbelt connector for quick release.
- 10.19.3 **Spec Muffler-** Schoenfeld #14272535 (-89 is not considered a compliant muffler) Minimum 1, must be un-altered and in otherwise in stock condition. Any car not running this muffler will be disallowed.

10.20 RIDE HEIGHT

- 10.20.1 No minimum ride height will be enforced.

10.21 PROTESTS

- 10.21.1 See Speedway Engine Protest procedures.
- 10.21.2 See Speedway Chassis Protest procedures.

10.22 MINIMUM WEIGHTS

- 10.22.1 Minimum total weight for 2 valves per cylinder engines as weighed with the driver will be 1.0 lbs per cc of engine displacement. Includes overbore.
- 10.22.2 Minimum total weight for cars with engines that have more than 2 valves per cylinder as weighed with the driver will be 1.05 lbs per cc of engine displacement. Includes overbore.
- 10.22.3 Maximum left side weight percentage as weighed with the driver will be 55.0%
- 10.22.4 Engine size must be noted in a minimum 6" tall letters on the hood or top left corner of the windshield in easy view of the scale master.
Declared Weight must be noted instead of motor size for Multiple Valve per cylinder cars.

10.23 RADIOS

10.23.1 One-way radios (scanners/ race scan) are required, must be on race control channel at all times.

10.23.2 Two-Way radios not permitted.